

LUCE

Version
Wall - 90 cm - Black - 800 m3/h

Designer

Collection
Design

EAN code
8034122348261



Photograph is for information purposes only
It may not correspond to the selected version.

FEATURES

- Scotch brite stainless steel (AISI 304)
- Black tempered glass
- Touch control + 24 h function
- Neon lighting
- Top filter, removable and washable
- Charcoal filter

OPTIONAL ACCESSORIES

- KACL.510#I**
Extension H700 Wall - Inox
- KACL.512#I**
Extension H960 Wall - Inox
- KACL.815**
Protective cleaning cloths for stainless steel (box 10 pcs)
- KACL.864**
Air flow conveyor for re-circulation version (Wall)

TECHNICAL FEATURES

- Installation type**
Wall
- Dimensions**
90 cm
- Finishing**
Scotch brite stainless steel (AISI 304)
Black tempered glass
- Motor**
800 m³/h
- Type of control**
Touch control
- Speed**
3 + boost
- Lighting**
Neon 1x21 W
- Filter**
3 x Metallic filter "Top" - Wall 285x301 mm
- Charcoal filter**
Square charcoal filter - Type 3 (optional)
- Minimum distance**
Gas hob: 63 cm
Electric hob: 52 cm

PACKAGING:WEIGHTS AND VOLUMES


- Gross weight**
26 kg
- Net weight**
21 kg
- Volumes**
0.26 m³
- Packaging size**
Length 995 mm
Height 440 mm
Depth 595 mm

CONSUMPTION AND CONNECTION FEATURES

- Maximum consumption**
320 W
- Voltage**
220-240V
- Frequency**
50-60Hz
- Plug type**
Shuko

MOTOR TECHNICAL SHEET

- Maximum capacity**
680 m³/h
I.E.C. 61591
- Maximum noise level**
68 dB(A)re1pW
I.E.C.60704-2-13
- Maximum pressure (Pa)**
500 Pa
- Max. motor power**
215 W
- ENERGY CLASS**
B



LUCE

Version
Wall - 90 cm - Black - 800 m3/h

Designer


Collection
Design

EAN code
8034122348261

MOTOR TECHNICAL SHEET

Motor speed	1	2	3	4
Noise level dB(A)re1pW-I.E.C.60704-2-13	49	56	62	68
Capacity (m3/h) I.E.C.61591	280	370	480	680
Maximum pressure (Pa)	390	420	480	500
Power (W)	132	153	175	215
Air outlet	150	150	150	150

CAPACITY / PRESSURE



LUCE


Version
Wall - 90 cm - Black - 800 m3/h

Designer

Collection
Design

EAN code
8034122348261

ENERGY LABEL



PF		
S	Falmec Spa	
M	Wall - 90 cm - Black - 800 m3/h	
AEC	79,1	kWh/a
EEC	B	
FDE	26,3	
FDEC	B	
LE	14,6	
LEC	D	
GFE	80,0	
GFEC	C	
Qmin	280,0	m³/h
Qmax	480,0	m³/h
Qboost	680,0	m³/h
SPEmin	49	dBa
SPEmax	62	dBa
SPEboost	68	dBa
PO	-	W
PS	0,48	W
PI		
F	1.1	
EEl	69,8	
Qbep	382,0	m³/h
Pbep	384	Pa
Qboost	680,0	m³/h
Wbep	155,1	W
WL	23,00	W
Emiddle	336	lux
Lwa-SPEmax	62	dBa

PF_Product fiche according to 65/2014 S_Supplier name / M_Model identification / AEC_Annual Energy Consumption (AEC hood) / EEC_Energy Efficiency class / FDE_Fluid Dynamic Efficiency (FDE hood) / FDEC_Fluid Dynamic Efficiency class / LE_Lighting Efficiency (LE hood) / LEC_Lighting Efficiency class / GFE_Grease Filtering Efficiency / GFEC_Grease Filtering Efficiency class / Qmin_Air flow (in m³/h) at min speed in normal use / Qmax_Air flow (in m³/h) at max speed in normal use / Qboost_Air flow (in m³/h) at intensive or boost setting (max air-flow) / SPEmin_Airborne acoustical A-weighted sound power emissions at min speed in normal use / SPEmax_Airborne acoustical A-weighted sound power emissions at max speed in normal use / SPEboost_Airbone acoustical A-weighted sound power emissions (in dB) at intensive or boost setting / PO_Power consumption in off mode (Po) / Ps_Power consumption in stand by mode (Ps). **PI_Additional information according to 66/2014** F_Time increase factor / EEl_Energy Efficiency Index / Qbep_Measured air flow rate at best efficiency point / Pbep_Measured air pressure at best efficiency point / Qboost_Maximun air flow / Wbep_Measured electric power input at best efficiency point / WL_Nominal power of the lighting system / Emiddle_Average illumination of the lighting system on the cooking surface / Lwa=SPEmax_Sound pressure level at the highest speed.