

Version	Comfort - Built-in - 60 cm - Inox - 800 m ³ /h
Design	Falmec Lab
Collection	No-Drop

TECHNICAL FEATURES

Materials/Finishes	Scotch brite stainless steel (AISI 430)
Technology	No-Drop patented anti-condensation system
Features	Side sound-absorbing panels for noise reduction Suction chamber enlarged Rotatable tempered glass flap with integrated control Protective flaps for the edge of the wall unit Emptyable liquid collector
Control	Touch control
Function	Extracting/Filtering
Lighting	Dynamic Light (2700K - 5600K) Dimmable lighting Strip LED 3,5 W - 2700 K / 5600 K
Filters	Anti-condensation no-drop filter in technopolymer Carbon.Zeo Microtech regenerable filter (optional)
Dimensions	60 cm
Minimum Electric hob distance	52 cm
Minimum Gas hob distance	52 cm

CONNECTION AND CONSUMPTION FUNCTIONS

Maximum consumption	280 W
Voltage/Frequency	220-240V 50-60Hz

MOTOR


Motor	800 m ³ /h
Maximum capacity	553 m ³ /h I.E.C.61591
Maximum sound level	63 dB (A)re1pW I.E.C. 60704-2-13
Energy class	A


WEIGHTS AND VOLUMES

Gross weight	13.3 kg
Net weight	10.4 kg
Volume	0.13 m ³
Packaging dimensions	L 705 x H 412 x P 465 mm



Photograph is for information purposes only. May not correspond to the selected version






Optional accessories


Code	Description
KACL.1039	Carbon.Zeo Microtech regenerable filter
KACL.1069	Ø150x600 - Soundproof tube (Virgola Touch Comfort/Virgola No-Drop Comfort)
KACL.1059	Conveyer for air outlet (Ø150)
KCVJN.01#3	Chimney h 120 mm - Inox
KCVJN.00#3	Telescopic chimney h 185 + h 185 mm - Inox
KCVJN.05#3	
KITRVIRCOM	
KACL.106	Glass shelf 60 cm

ENGINE SPECIFICATIONS

Motor speed	1	2	3	4
Noise dB(A) re1pW I.E.C. 60704-2-13	51	57	63	67
Capacity	305	423	553	680
Maximum pressure (Pa)	410	440	460	480
Motor power (W)	150	180	200	215
Air outlet	150	150	150	150

FLOW RATE / PRESSURE





PF		
S	Falmec Lab	
M	Comfort - Built-in - 60 cm - Inox - 800 m3/h	
AEC	48.20	kWh/a
EEC	A	
FDE	30.50	
FDEC	A	
LE	44.00	
LEC	A	
GFE	70	
GFEC	D	
Qmin	305	m ³ /h
Qmax	553	m ³ /h
Qboost	680	m ³ /h
SPEmin	51	dBa
SPEmax	63	dBa
SPEboost	67	dBa
PO		
PS	0.28	W
PI		
F	0.90	
EEL	51.40	
Qbep	374	m ³ /h
Pbep	408	Pa
Qboost	680	m ³ /h
Wbep	139	W
WL	3.50	W
Emiddle	154	lux
Lwa-SPEmax	63	dBa

PF_Scheda prodotto conforme a 65/2014 S_Supplier name / M_Model identification / AEC_Annual Energy Consumption (AEC hood) / EEC_Energy Efficiency class / FDE_Fluid Dynamic Efficiency (FDE hood) / FDEC_Fluid Dynamic Efficiency class / LE_Lighting Efficiency (LE hood) / LEC_Lighting Efficiency class / GFE_Grease Filtering Efficiency / GFEC_Grease Filtering Efficiency class / Qmin_Air flow (in m³/h) at min speed in normal use / Qmax_Air flow (in m³/h) at max speed in normal use / Qboost_Air flow (in m³/h) at intensive or boost setting (max air-flow) / SPEmin_Airborne acoustical A-weighted sound power emissions at min speed in normal use / SPEmax_Airborne acoustical A-weighted sound power emissions at max speed in normal use / SPEboost_Airborne acoustical A-weighted sound power emissions (in dB) at intensive or boost setting / P0_Power consumption in off mode (Po) / Ps_Power consumption in stand by mode (Ps).

PI_Additional information according to 66/2014 Calculation methods: EN 61591:2020 F_Time increase factor / EEL_Energy Efficiency Index / Qbep_Measured air flow rate at best efficiency point / Pbep_Measured air pressure at best efficiency point / Qboost_Maximum air flow / Wbep_Measured electric power input at best efficiency point / WL_Nominal power of the lighting system / Emiddle_Average illumination of the lighting system on the cooking surface / Lwa=SPEmax_Sound pressure level at the highest speed.