

Version	Corner - 90 cm - Inox - 800 m3/h
Design	Falmec Lab
Collection	Design

TECHNICAL FEATURES

Materials/Finishes	Scotch brite stainless steel (AISI 304)
Materials/Finishes	Lower frame finishing: stainless steel
Control	Electronic control
Function	Extracting/Filtering
Lighting	Dynamic Light (2700K - 5600K)
	Dimmable lighting
	LED 3x1,2 W - 2700 K / 5600 K
Filters	Top filter, removable and washable
	Charcoal filter
Dimensions	90 cm
Minimum Electric hob distance	52 cm
Minimum Gas hob distance	65 cm
Notes	From 04.11.2024 the dynamic and dimmable light is included.



Photograph is for information purposes only. May not correspond to the selected version

CONNECTION AND CONSUMPTION FUNCTIONS


Maximum consumption	280 W
Voltage/Frequency	220-240V 50-60Hz
Plug	Shuko

MOTOR

Motor	800 m³/h
Maximum capacity	680 m³/h I.E.C.61591
Maximum sound level	62 dB (A)re1pW I.E.C. 60704-2-13
Energy class	B

WEIGHTS AND VOLUMES

Gross weight	22 kg
Net weight	15 kg
Volume	0.51 m3
Packaging dimensions	L 1115 x H 417 x P 1100 mm




Optional accessories


<i>Code</i>	<i>Description</i>
KACL.560#I	Extension H850 - Wall
KACL.815	Protective cleaning cloths for stainless steel (box 10 pcs)

ENGINE SPECIFICATIONS

Motor speed	1	2	3	4
Noise dB(A) re1pW I.E.C. 60704-2-13	49	56	62	68
Capacity	280	370	480	680
Maximum pressure (Pa)	390	420	480	500
Motor power (W)	132	153	175	215
Air outlet	150	150	150	150

FLOW RATE / PRESSURE





PF		
S	Falmecc Lab	
M	Corner - 90 cm - Inox - 800 m3/h	
AEC	67	kWh/a
EEC	B	
FDE	26.3	
FDEC	B	
LE	18.3	
LEC	C	
GFE	96	
GFEC	A	
Qmin	280	m³ /h
Qmax	480	m³ /h
Qboost	680	m³ /h
SPEmin	49	dBa
SPEmax	62	dBa
SPEboost	68	dBa
PO	0	W
PS	0.48	W
PI		
F	1.1	
EEL	64.3	
Qbep	382	m³ /h
Pbep	384	Pa
Qboost	680	m³ /h
Wbep	155.1	W
WL	6.5	W
Emiddle	119	lux
Lwa-SPEmax	62	dBa

PF_Scheda prodotto conforme a 65/2014 S_Vendor name / M_Project identification / AEC_Yearly energy consumption (AEC) hood / EEC_Energy efficiency class / FDE_Fluid dynamic efficiency (FDE) hood / FDEC_Fluid dynamic efficiency class / LE_Light efficiency (LE) hood / LEC_Light efficiency class of luminous efficiency / GFE_Fat filtration efficiency / GFEC_Fat filtration efficiency class / Qmin_Airflow (in m³/h) at minimum power under normal use conditions / Qmax_Airflow (in m³/h) at maximum power under normal use conditions / Qboost_Airflow (in m³/h) at the intensive power / SPEmin_A-weighted sound power of airborne noise emissions at the minimum power under normal use conditions / SPEmax_A-weighted sound power of airborne noise emissions at the maximum power under normal use conditions / SPEboost_A-weighted sound power of airborne noise emissions under intensive or boost use conditions / PO_CPower consumption in off mode (Po) / Ps_CPower consumption in standby mode (Ps).

PI_Additional information in accordance with 66/2014 4 F_Fattore di incremento nel tempo / EEL_Indice di efficienza energetica / Qbep_Velocità del flusso d'aria misurato nel punto di efficienza migliore / Pbep_Pressione dell'aria misurata nel punto di efficienza migliore / Qboost_Flusso d'aria massimo / Wbep_Ingresso energia elettrica misurato nel punto di efficienza migliore / WL_Potenza nominale del sistema luminoso / Emiddle_Illuminazione media del sistema luminoso sulla superficie di cottura / Lwa=SPEmax_Livello di pressione sonora alla potenza massima.