

Version	Wall - 85 cm - Satin Black - 800 m3/h
Collection	Design

TECHNICAL FEATURES

Materials/Finishes	Painted black steel
Materials/Finishes	Black glass satin finishing
Materials/Finishes	Tempered white glass with Stainless Steel central band
Features	Opening frontal
Control	Electronic control
Function	Extracting/Filtering
Chimney	Possible to duct wall mounted from rear Optional chimney
Lighting	Dimmable lighting Dynamic Light (2700K - 5600K) LED 2x1,2 W - 2700 K / 5600 K
Filters	Metallic grease filter, removable and washable Combined regenerable Carbon.Zeo filter (optional) Charcoal filter
Dimensions	85 cm
Minimum Electric hob distance	52 cm
Minimum Gas hob distance	52 cm
Notes	Dynamic and dimmable Led light from 03.04.24



Photograph is for information purposes only. May not correspond to the selected version

CONNECTION AND CONSUMPTION FUNCTIONS


Maximum consumption	280 W
Voltage/Frequency	220-240V 50-60Hz
Plug	Shuko

MOTOR

Motor	800 m³/h
Maximum capacity	750 m³/h I.E.C.61591
Maximum sound level	58 dB (A)re1pW I.E.C. 60704-2-13
Energy class	A

WEIGHTS AND VOLUMES

Gross weight	30 kg
Net weight	25 kg
Volume	0.27 m3
Packaging dimensions	L 950 x H 442 x P 655 mm




Optional accessories


Code	Description
KACL.958#NF	External Carbon.Zeo filter unit for sloped hoods (Black)
KCQAN.00#I	Chimney - Inox
KCQAN.00#N	Chimney - Black
KACL.1059	Conveyer for air outlet (Ø150)

ENGINE SPECIFICATIONS

Motor speed	1	2	3	4
Noise dB(A) re1pW I.E.C. 60704-2-13	46	53	58	66
Capacity	295	390	500	750
Maximum pressure (Pa)	390	440	490	510
Motor power (W)	130	150	178	224
Air outlet	150	150	150	150

FLOW RATE / PRESSURE





PF		
S		
M	Wall - 85 cm - Satin Black - 800 m3/h	
AEC	57.7	kWh/a
EEC	A	
FDE	29.4	
FDEC	A	
LE	21.6	
LEC	B	
GFE	82	
GFEC	C	
Qmin	295	m³ /h
Qmax	500	m³ /h
Qboost	750	m³ /h
SPEmin	46	dBa
SPEmax	58	dBa
SPEboost	66	dBa
PO	0	W
PS	0.48	W
PI		
F	0.9	
EEL	53.2	
Qbep	430	m³ /h
Pbep	404	Pa
Qboost	750	m³ /h
Wbep	164	W
WL	5.3	W
Emiddle	114	lux
Lwa-SPEmax	58	dBa

PF_Scheda prodotto conforme a 65/2014 S_Vendor name / M_Project identification / AEC_Yearly energy consumption (AEC) hood / EEC_Energy efficiency class / FDE_Fluid dynamic efficiency (FDE) hood / FDEC_Fluid dynamic efficiency class / LE_Light efficiency (LE) hood / LEC_Light efficiency class of luminous efficiency / GFE_Fat filtration efficiency / GFEC_Fat filtration efficiency class / Qmin_Airflow (in m³/h) at minimum power under normal use conditions / Qmax_Airflow (in m³/h) at maximum power under normal use conditions / Qboost_Airflow (in m³/h) at the intensive power / SPEmin_A-weighted sound power of airborne noise emissions at the minimum power under normal use conditions / SPEmax_A-weighted sound power of airborne noise emissions at the maximum power under normal use conditions / SPEboost_A-weighted sound power of airborne noise emissions under intensive or boost use conditions / P0_CPower consumption in off mode (Po) / Ps_CPower consumption in standby mode (Ps).

PI_Additional information in accordance with 66/2014 4 F_Factor of increase over time / EEL_Energy Efficiency Index / Qbep_Airflow speed measured at best efficiency point / Pbep_Air pressure measured at best efficiency point / Qboost_Full airflow / Wbep_Energy input measured at best efficiency point / WL_Nominal power of lighting system / Emiddle_Average illumination of lighting system on cooking surface / Lwa=SPEmax_Loise pressure level at maximum power