


### 3. TECHNICAL DATA

Below is an example of the nameplate:

|                                                   |                |                                                                                                                                                                                                                                                                                                                                        |  |
|---------------------------------------------------|----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| <b>avintage</b> ●●●                               |                | <b>ELECTRIC DIAGRAM</b><br>Schéma électrique<br><br><br>Made in PRC<br>FRIO Entreprise / Climadiff -<br>143 Boulevard Pierre Lefaucheux -<br>72230 ARNAGE - France |  |
| Référence                                         | AVU53PREMIUM   |                                                                                                                                                                                                                                                                                                                                        |  |
| Service Ref                                       | AVU53PREMIUM/1 |                                                                                                                                                                                                                                                                                                                                        |  |
| S/N                                               |                |                                                                                                                                                                                                                                                                                                                                        |  |
| Modèle usine                                      | JG46           |                                                                                                                                                                                                                                                                                                                                        |  |
| Classe climatique                                 | N/SN           |                                                                                                                                                                                                                                                                                                                                        |  |
| Volume Total Net                                  | 135L           |                                                                                                                                                                                                                                                                                                                                        |  |
| Consommation d'énergie annuelle                   | 157 kWh/an     |                                                                                                                                                                                                                                                                                                                                        |  |
| Consommation jour d'énergie à 16°C                | 0,119 kWh/24h  |                                                                                                                                                                                                                                                                                                                                        |  |
| Consommation jour d'énergie à 32°C                | 0,562 kWh/24h  |                                                                                                                                                                                                                                                                                                                                        |  |
| Gaz réfrigérant / Quantité                        | R600A/35g      |                                                                                                                                                                                                                                                                                                                                        |  |
| Agent isolant                                     | Cyclopentane   |                                                                                                                                                                                                                                                                                                                                        |  |
| Voltage                                           | 220-240V AC    |                                                                                                                                                                                                                                                                                                                                        |  |
| Fréquence                                         | 50 Hz          |                                                                                                                                                                                                                                                                                                                                        |  |
| Ampérage                                          | 1.2 A          |                                                                                                                                                                                                                                                                                                                                        |  |
| Puissance maximum                                 | 80W            |                                                                                                                                                                                                                                                                                                                                        |  |
| Puissance de la lampe                             | Max 3 W        |                                                                                                                                                                                                                                                                                                                                        |  |
| Classe de protection contre les chocs électriques | ⓘ              |                                                                                                                                                                                                                                                                                                                                        |  |

The nameplate attached to the inside or rear of the appliance (depending on the model) includes the entire information specific to your appliance.

We recommend that you make a note of its serial number in this booklet prior to installation, so that you can refer to it later (technical work, request for assistance, etc.).



Once the appliance is installed and loaded, access to it is not so easy.

**CAUTION: no assistance can be provided without this information.**

### 4. INSTALLATION INSTRUCTIONS

#### Before using this appliance

- Remove the exterior and interior packing.
- Before connecting the appliance to the power source, let it stand upright for approximately 24 hours. This will reduce the possibility of a malfunction in the cooling system from handling during transportation.
- Clean the interior surface with lukewarm water using a soft cloth.
- When disposing your appliance, please choose an authorized disposal site.
- Use two or more suitably qualified people to move and install the appliance. Failure to do so can result in back or other injury.
- Place your wine cooler on a position that is strong enough to support it when it is fully loaded. To level your wine cooler, adjust the front leveling leg at the bottom of the wine cooler.
- Adequate ventilation is required, do not block the front air outlet.
- Not designed for placement in adage or basement.
- The appliance is for indoor use only.
- This wine cellar is designed for free-standing or built-under installation.
- Connect the cellar to a single socket and be careful to support it, so that your wine cellar is perfectly level (use of a spirit level is recommended). This will prevent any movement due to instability, causing noise and vibration, and will ensure that the door seals perfectly.

- This appliance is intended to be used exclusively for the storage of wine.
- This appliance is using flammability refrigerant. So never damage the cooling pipe work during the transportation.

#### Attention

- Store wine in sealed bottles.
- Do not overload the cabinet.
- Do not open the door unless necessary.
- Do not cover shelves with aluminum foil or any other shelf material which may prevent air circulation.
- Should the wine cooler be left empty for long periods it is suggested that the appliance is unplugged, and after careful cleaning, leave the door ajar to allow air to circulate inside the cabinet in order to avoid possible condensation, mold or odors forming.

**CAUTION:** please keep the appliance away from substance, which can cause ignition.


#### Ambient room temperature limits

This appliance is designed to operate in ambient temperatures specified by its temperature class marked on the rating plate.

| CLASS              | SYMBOL | AMBIENT TEMPERATURES RANGE (°C) |
|--------------------|--------|---------------------------------|
| Extended temperate | SN     | From +10 to +32                 |
| Temperate          | N      | From +16 to +32                 |
| Subtropical        | ST     | From +16 to +38                 |
| Tropical           | T      | From +16 to +43                 |

This refrigerating appliance is intended to be used at ambient temperatures ranging from 10 °C to 38 °C

#### Built-in installation drawings






Improper installation of your appliance will not allow the push-pull system to function properly to open or close the door. Make sure to follow the instructions above.

### Fixation to the furniture

WARNING: Risk of the product tipping over when the door is opened, the appliance must be fixed to the furniture.


In order to ensure the stability of your device, use the supplied bracket according to the diagram below.



1. Remove the cover caps as shown in picture A.
2. With the help of the screws (1), place the fixing plate (2) as shown in picture B. Do not tighten the screws (1) to facilitate the adjustment of the fixing plate (2).
3. With the help of the screws (3), fix the fixing plate against the furniture as shown in picture C.
4. Fasten the screws (1) more tightly to ensure that the appliance is held securely.

### Opening push-pull system

Press twice in succession in the opening area at the upper left zone. Be careful not to leave more than one second between the two pressing. This is normal that there is a delay between touching your wine cellar and the moment the door opens.



Moreover, the system is electronic; it does not require any adjustment on your side.



Before closing the door carefully, **please wait for the opening system to return to its original position**. Forcing when closing **may damage** the push-pull system.